


Non-Insulated Butt Splice Connectors (BM)

Brand	KF®
Finish/Coating	Tinned
Base Materials	Copper
Insulation Material	N/A
Brazed	Seam
Wire/Cable Type	Regular Wire
Color Code	Standard
MOQ	1000Pcs/item
Payment Terms	Based on orders
Delivery	FOB/CIF/DDP



Spec(American AWG)	16	14	12	10	8	6	4	2	1/0	2/0	3/0	4/0
Spec(JIS AWG)	1.5	2.5	4	6	10	16	25	35	50	70	95	120
Spec(DIN AWG)												
Spec(GB mm²)												
Max Current	18	30	35	50	70	95	125	170	230	265	310	360
Spec(American AWG)	250-300MCM			300-350MCM			400MCM			500MCM		
Spec(JIS AWG)	150			185			240			300		
Spec(DIN AWG)												
Spec(GB mm²)												
Max Current	445			505			545			620		



Wire Range	SKU#	MFG#	Dimension(mm)						Tool	pcs/pack
			L		D		d			
A.W.G. 16 1.5mm ²	KFBOM10	BM1.5	0.866	22.0	0.157	4.0	0.094	2.4	IZUMI 5N18	1000
A.W.G. 14 2.5mm ²	KFBOM20	BM2.5	0.866	22.0	0.169	4.3	0.106	2.7	IZUMI 5N18	1000
A.W.G. 12 4mm ²	KFBOM30	BM4	0.984	25.0	0.189	4.8	0.122	3.1	IZUMI 5N18	1000
A.W.G. 10 6mm ²	KFBOM40	BM6	0.984	25.0	0.217	5.5	0.15	3.8	IZUMI 5N18	500
A.W.G. 8 10mm ²	KFBOM50	BM10	0.984	25.0	0.272	6.9	0.185	4.7	IZUMI 5N18	500
A.W.G. 6 16mm ²	KFBOM60	BM16	1.142	29.0	0.307	7.8	0.22	5.6	IZUMI 5N18	500
A.W.G. 4 25mm ²	KFBOM70	BM25	1.142	29.0	0.374	9.5	0.28	7.1	OPT THX-185	250
A.W.G. 2 35mm ²	KFBOM80	BM35	1.378	35.0	0.433	11.0	0.323	8.2	OPT THX-185	200
A.W.G. 1/0 50mm ²	KFBOM90	BM50	1.378	35.0	0.492	12.5	0.374	9.5	OPT THX-185	100
A.W.G. 2/0 70mm ²	KFBOMA0	BM70	1.772	45.0	0.591	15.0	0.453	11.5	OPT THX-185	100
A.W.G. 3/0 95mm ²	KFBOMB0	BM95	1.85	47.0	0.669	17.0	0.531	13.5	OPT THX-185	50
A.W.G. 4/0 120mm ²	KFBOMC0	BM120	2.047	52.0	0.787	20.0	0.614	15.6	OPT THX-185	30
A.W.G.250/300MCM 150mm ²	KFBOMD0	BM150	2.323	59.0	0.827	21.0	0.65	16.5	OPT THX-185	10
A.W.G.300/350MCM 185mm ²	KFBOME0	BM185	2.559	65.0	0.929	23.6	0.724	18.4	OPT THX-185	10
A.W.G.400MCM 240mm ²	KFBOMF0	BM240	2.953	75.0	1.039	26.4	0.835	21.2	OPT THX-185	10
A.W.G.500MCM 300mm ²	KFBOMG0	BM300	3.543	90.0	1.126	28.6	0.921	23.4	OPT THX-185	5
A.W.G.600/750MCM 400mm ²	KFBOMH0	BM400	4.173	106.0	1.291	32.8	1.055	26.8	OPT THX-185	5