


Heat Shrink-Insulated Single Crimp Flange Spade Terminals

Brand	KF®
Finish/Coating	Tinned
Base Materials	Copper, PE
Insulation Material	N/A
Brazed	Seam
Wire/Cable Type	Regular Wire
Color Code	Standard
MOQ	1000Pcs/item
Payment Terms	Based on orders
Delivery	FOB/CIF/DDP



Spec (American AWG)	22-16	16-14	12-10
Spec (JIS AWG)	1.25	2	5.5
Spec (DIN AWG)	1	2.5	4.0-6.0
Spec (GB mm²)	0.5-1.5	2.5	6
Max Current	19	27	48
Operating Voltage	600V		
Heat Shrinkable Temperature	150°C		
Working Temperature	-40~+105°C		



Wire Range	SKU#	MFG#	Stud Size		Dimension(mm)						Color	Tool	pcs/pack	
			USA	Meri	d2		B		L					T
A.W.G. 22-16 0.5~1.5mm²	KFSH210	FSH1.25-3.5	#6	3.5	0.146	3.7	0.256	6.5	1.299	33.0	0.03 (0.75)	red	IZUMI 3#	1000
	KFSH211	FSH1.25-4	#8	4.0	0.169	4.3	0.276	7.0	1.299	33.0				1000
	KFSH212	FSH1.25-5	#10	5.0	0.209	5.3	0.374	9.5	1.299	33.0				1000
A.W.G. 16-14 1.5~2.5mm²	KFSH220	FSH2-3.5	#6	3.5	0.146	3.7	0.276	7.0	1.299	33.0	0.031 (0.8)	blue	IZUMI 4#	1000
	KFSH221	FSH2-4	#8	4.0	0.169	4.3	0.276	7.0	1.299	33.0				1000
	KFSH222	FSH2-5	#10	5.0	0.209	5.3	0.374	9.5	1.299	33.0				1000
A.W.G. 12-10 4~6mm²	KFSH230	FSH5.5-3.5	#6	3.5	0.146	3.7	0.335	8.5	1.398	35.5	0.039 (1.0)	yellow	IZUMI 5#	1000
	KFSH231	FSH5.5-4	#8	4.0	0.169	4.3	0.335	8.5	1.398	35.5				1000
	KFSH232	FSH5.5-5	#10	5.0	0.209	5.3	0.354	9.0	1.398	35.5				1000