


Vinyl-Insulated Single Crimp (Easy Entry) Flange Spade Terminals

Brand	KF®
Finish/Coating	Tinned
Base Materials	Copper, PVC
Insulation Material	N/A
Brazed	Seam
Wire/Cable Type	Regular Wire
Color Code	Standard
MOQ	1000Pcs/item
Payment Terms	Based on orders
Delivery	FOB/CIF/DDP



Spec (American AWG)	22-16	16-14	12-10
Spec (JIS AWG)	1.25	2	5.5
Spec (DIN AWG)	1	2.5	4.0-6.0
Spec (GB mm²)	0.5-1.5	2.5	6
Max Current	19	27	48
Operating Voltage	600V		
Temperature Withstand	75°C		



Wire Range	SKU#	MFG#	Stud Size		Dimension(mm)								Color	Tool	pcs/pack			
			USA	Meri	d2	B	L	F	H	D	T							
A.W.G. 22-16 0.5~1.5mm²	KFSE210	FSVE1.25-3.5	#6	3.5	0.146	3.7	0.827	21.0	0.886	22.5	0.256	6.5	0.433 (11.0)	0.157 (4.0)	0.03 (0.75)	red	IZUMI 3#	1000
	KFSE211	FSVE1.25-4	#8	4	0.169	4.3	0.984	25.0	0.886	22.5	0.256	6.5						1000
	KFSE212	FSVE1.25-5	#10	5	0.209	5.3	1.142	29.0	0.886	22.5	0.256	6.5						1000
A.W.G. 16-14 1.5~2.5mm²	KFSE220	FSVE2-3.5	#6	3.5	0.146	3.7	0.846	21.5	0.906	23.0	0.256	6.5	0.453 (11.5)	0.177 (4.5)	0.031 (0.8)	blue	IZUMI 4#	1000
	KFSE221	FSVE2-4	#8	4	0.169	4.3	1.004	25.5	0.906	23.0	0.256	6.5						1000
	KFSE222	FSVE2-5	#10	5	0.209	5.3	1.161	29.5	0.906	23.0	0.256	6.5						1000
A.W.G. 12-10 4~6mm²	KFSE230	FSVE5.5-3.5	#6	3.5	0.146	3.7	0.945	24.0	1.403	26.5	0.295	7.5	0.511 (14.0)	0.256 (6.5)	0.039 (1.0)	yellow	IZUMI 5#	1000
	KFSE231	FSVE5.5-4	#8	4	0.169	4.3	1.102	28.0	1.403	26.5	0.295	7.5						1000
	KFSE232	FSVE5.5-5	#10	5	0.209	5.3	1.26	32.0	1.403	26.5	0.295	7.5						1000