

Heat Shrink-Insulated Single Crimp Lipped Blade Terminals

Brand	KF [®]
Finish/Coating	Tinned
Base Materials	Copper, PE
Insulation Material	N/A
Brazed	Seam
Wire/Cable Type	Regular Wire
Color Code	Standard
MOQ	1000Pcs/item
Payment Terms	Based on orders
Delivery	FOB/CIF/DDP



Spec (American AWG)	22-16	16-14	12-10
Spec (JIS AWG)	1.25	2	5.5
Spec (DIN AWG)	1	2.5	4.0-6.0
Spec (GB mm ²)	0.5-1.5	2.5	6
Max Current	19	27	48
Operating Voltage	600V		
Heat Shrinkable Temperature	150°C		
Working Temperature	-40~+105°C		



Wire Range	SKU#	MFG#	Dimension(mm)						Color	Tool	pcs/pack	
			B		D		L					T
A.W.G. 22-16 0.5~1.5mm ²	KFSH610	LBH1.25-3	0.118	3.0	0.197	5.0	1.496	38.0	0.03 (0.75)	red	IZUMI 3#	1000
	KFSH611	LBH1.25-4.6	0.181	4.6	0.197	5.0	1.496	38.0				1000
A.W.G. 16-14 1.5~2.5mm ²	KFSH620	LBH2-3	0.118	3.0	0.236	6.0	1.535	39.0	0.031 (0.8)	blue	IZUMI 4#	1000
	KFSH621	LBH2-4.6	0.181	4.6	0.236	6.0	1.535	39.0				1000
A.W.G. 12-10 4~6mm ²	KFSH630	LBH5.5-3	0.118	3.0	0.256	6.5	1.575	40.0	0.039 (1.0)	yellow	IZUMI 5#	1000
	KFSH631	LBH5.5-4.6	0.181	4.6	0.256	6.5	1.575	40.0				500