


Heat Shrink-Insulated Single Crimp Spade Terminals

Brand	KF [®]
Finish/Coating	Tinned
Base Materials	Copper, PE
Insulation Material	N/A
Brazed	Seam
Wire/Cable Type	Regular Wire
Color Code	Standard
MOQ	1000Pcs/item
Payment Terms	Based on orders
Delivery	FOB/CIF/DDP



Spec (American AWG)	22-16	16-14	12-10
Spec (JIS AWG)	1.25	2	5.5
Spec (DIN AWG)	1	2.5	4.0-6.0
Spec (GB mm ²)	0.5-1.5	2.5	6
Max Current	19	27	48
Operating Voltage	600V		
Heat Shrinkable Temperature	150°C		
Working Temperature	-40~+105°C		



Wire Range	SKU#	MFG#	Stud Size		Dimension(mm)						Color	Tool	pcs/pack	
			USA	Meric	d2		W		L					T
A.W.G. 22-16 0.5~1.5mm ²	KFSH010	SHB1.25-3	#4	3.0	0.126	3.2	0.217	5.5	1.299	33.0	0.03 (0.75)	red	IZUMI 3#	1000
	KFSH011	SHBS1.25-3.5	#6	3.5	0.146	3.7	0.217	5.5	1.299	33.0				1000
	KFSH012	SHBL1.25-3.5	#6	3.5	0.146	3.7	0.256	6.5	1.299	33.0				1000
	KFSH013	SHBS1.25-4	#8	4.0	0.169	4.3	0.256	6.5	1.299	33.0				1000
	KFSH014	SHBM1.25-4	#8	4.0	0.169	4.3	0.276	7.0	1.299	33.0				1000
	KFSH015	SHBL1.25-4	#8	4.0	0.169	4.3	0.315	8.0	1.299	33.0				1000
	KFSH016	SHBS1.25-5	#10	5.0	0.209	5.3	0.315	8.0	1.299	33.0				1000
	KFSH017	SHBL1.25-5	#10	5.0	0.209	5.3	0.374	9.5	1.299	33.0				1000
	KFSH018	SHBS1.25-6	1/4"	6.0	0.252	6.4	0.374	9.5	1.299	33.0				1000
	KFSH019	SHBL1.25-6	1/4"	6.0	0.252	6.4	0.472	12.0	1.535	39.0				1000
A.W.G. 16-14 1.5~2.5mm ²	KFSH020	SHB2-3	#4	3.0	0.126	3.2	0.217	5.5	1.299	33.0	0.031 (0.8)	blue	IZUMI 4#	1000
	KFSH021	SHBS2-3.5	#6	3.5	0.146	3.7	0.217	5.5	1.299	33.0				1000
	KFSH022	SHBL2-3.5	#6	3.5	0.146	3.7	0.276	7.0	1.299	33.0				1000
	KFSH023	SHBS2-4	#8	4.0	0.169	4.3	0.256	6.5	1.299	33.0				1000
	KFSH024	SHBM2-4	#8	4.0	0.169	4.3	0.276	7.0	1.299	33.0				1000
	KFSH025	SHBL2-4	#8	4.0	0.169	4.3	0.315	8.0	1.299	33.0				1000
	KFSH026	SHBS2-5	#10	5.0	0.209	5.3	0.315	8.0	1.299	33.0				1000
	KFSH027	SHBL2-5	#10	5.0	0.209	5.3	0.374	9.5	1.299	33.0				1000
	KFSH028	SHBS2-6	1/4"	6.0	0.252	6.4	0.374	9.5	1.299	33.0				1000
	KFSH029	SHBL2-6	1/4"	6.0	0.252	6.4	0.472	12.0	1.535	39.0				1000
A.W.G. 12-10 4~6mm ²	KFSH030	SHB5.5-3.5	#6	3.5	0.146	3.7	0.335	8.5	1.437	36.5	0.039 (1.0)	yellow	IZUMI 5#	1000
	KFSH031	SHBS5.5-4	#8	4.0	0.169	4.3	0.335	8.5	1.437	36.5				1000
	KFSH032	SHBL5.5-4	#8	4.0	0.169	4.3	0.374	9.5	1.437	36.5				1000
	KFSH033	SHB5.5-5	#10	5.0	0.209	5.3	0.354	9.0	1.437	36.5				1000
	KFSH034	SHBS5.5-6	1/4"	6.0	0.252	6.4	0.354	9.0	1.437	36.5				1000
	KFSH035	SHBL5.5-6	1/4"	6.0	0.252	6.4	0.472	12.0	1.634	41.5				500
	KFSH036	SHB5.5-8	5/16"	8.0	0.331	8.4	0.551	14.0	1.594	40.5				500